

Fiber Optic Closure



For detailed inquiry
please contact our
sales team at:
market@jfopt.com

MODEL : Dome JFCL-D1

● **Features :**

- ◆ **The box add aging-resistant in imported high tensile construction plastic out-faster is made up of stainless steel.**
- ◆ **Overlap structure in splicing tray easy to install**
- ◆ **Suitable for ordinary fiber and ribbon fiber**
- ◆ **Perfect leak proofness and fine function**
- ◆ **Perfect and reliable sealing operations**
- ◆ **Fiber-bending radium guaranteed more than 40mm**
- ◆ **Full accessories for convenient operations**
- ◆ **Fiber optic splice closure can be used repeatedly**
- ◆ **High reliability**
- ◆ **For aerial, and direct buried applications**

● **Specifications :**

- ◆ **Temperature: -40 to +80 degrees Celsius**
- ◆ **Atmosphere: 70 to 106kpa**
- ◆ **Sealing property at normal temperature: Internal pressure: 70 KPa, without decrease in 72 hours**
- ◆ **High temperature sealing property: internal pressure: 70KPa, without decrease in 168 hours at 60 degree**
- ◆ **Insulated resistance: $>2 \times 10^4 M\Omega$**
- ◆ **Intensity: 15KV (DC) not being broken down, has no flying arc.**
- ◆ **Add ional Loss: No additional loss when optic fibers are winded in the splice trays**
- ◆ **The-ageing time of the material of the enclosure is beyond 20 years**

Description	Number of inlet/outlet ports	Capacity(Cores)	Size
Fiber closure, dome type JFCL-D1	4	Bunchy: 6-48	Φ288x178