



## Fiber Optical Patch Cord, LC-LC, Simplex



### Features

- PC, UPC or APC polishing
- Single mode fiber: ITU- T G.652, or G655, or G657
- Multi mode fiber, ITU-TG.651
- Standard housing, ceramic ferrule
- Cable diameter: 0.9mm, 2.0mm, 3.0mm or customized
- Fiber type: 9/125 μm (OS1), or 62.5/125μm (OM1), or 50/125μm (OM2, OM3 and OM3+)
- Insertion loss: Less than 0.3dB
- Return loss:
  - UPC SM larger than 50dB
  - PC SM larger than 45dB
  - APC SM larger than 60 dB
  - PC MM larger than 20 dB
- Repeatability: Less than 0.2 dB
- Changeability: Less than 0.1 dB
- Operating temperature range: -20°C ~ 70°C
- Storage temperature range: -40°C ~ 80°C
- Color of the jacket: SM yellow, OM1, OM2 orange, OM3 aqua, or customized
- Material of the jacket: PVC or LSZH or customized



No.	Description	Qty
①	Dust cap	2
②	Connector	2
③	Optical Cable	1

**For detailed inquiry please contact our sales team at [market@jfopt.com](mailto:market@jfopt.com)**

Shenzhen Jiafu Optical Communication Co., Ltd

Add: 2<sup>nd</sup> Floor, Building A, Huilongda Industrial Park, Shuitian Community, Shiyuan Street, Bao'an District, Shenzhen City, Guangdong Province, China

Tel: 86-755-8357 0641 & 86-755-8357 0652 Fax: 86-755-8357 0649